

# **CAPCO**

## **QS SPECIFICATIONS**

### **EXPOSED TEE SUSPENDED CEILINGS**

#### **Thermotex – 600 x 600 x 34mm**

Supply and install 600 x 600 x 34mm Thermotex Ripple White vinylclad 9mm gypsum ceiling tiles with aluminium foil backing and 25mm thick fire-retardant polystyrene adhered to back laid onto CKM T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

#### **Thermotex – 1200 x 600 x 34mm**

Supply and install 1200 x 600 x 34mm Thermotex Ripple White vinylclad 9mm gypsum ceiling tiles with aluminium foil backing and 25mm thick fire-retardant polystyrene adhered to back laid onto CKM T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.