CAPCO

QS SPECIFICATIONS

EXPOSED TEE SUSPENDED CEILINGS

DAIKEN EXCEL-TONE MOISTURE RESISTANT MINERAL FIBRE ACOUSTIC TILES

600 x 600 x 15mm

NEW NDF (Non Directional Fissured)

Supply and install Daiken Excel-Tone Moisture Resistant 99% relative humidity resistant pre-painted white acoustic mineral fibre ceiling tiles 600 x 600 x 15mm with New NDF finish and square edge (revealed edge) laid onto CKM T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

CONSTELLATION

Supply and install Daiken Excel-Tone Moisture Resistant 99% relative humidity resistant pre-painted white acoustic mineral fibre ceiling tiles 600 x 600 x 15mm with Constellation finish and square edge (revealed edge) laid onto CKM T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

CAPCO

QS SPECIFICATIONS

EXPOSED TEE SUSPENDED CEILINGS

DAIKEN EXCEL-TONE MOISTURE RESISTANT MINERAL FIBRE ACOUSTIC TILES

1200 x 600 x 15mm

NEW NDF (Non Directional Fissured)

Supply and install Daiken Excel-Tone Moisture Resistant 99% relative humidity resistant pre-painted white acoustic mineral fibre ceiling tiles 1200 x 600 x 15mm with New NDF finish and square edge laid onto CKM T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

CONSTELLATION

Supply and install Daiken Excel-Tone Moisture Resistant 99% relative humidity resistant pre-painted white acoustic mineral fibre ceiling tiles 1200 x 600 x 15mm with Constellation finish and square edge laid onto CKM T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.