CAPCO

QS SPECIFICATIONS

EXPOSED TEE SUSPENDED CEILINGS

Pyroceil – 600 x 600 x 6mm

Supply and install 600 x 600mm x 6mm Pyroceil white fire-retardant paint surface non-combustible calcium silicate sealed backed tiles. Rated A/A1/1 in terms of SANS 10177-Part 5. Laid onto CKM fire-rated T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 X 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

Pyroceil – 1200 x 600 x 6mm

Supply and install 1200 x 600mm x 6mm Pyroceil white fire-retardant paint surface non-combustible calcium silicate sealed backed tiles. Rated A/A1/1 in terms of SANS 10177-Part 5. Laid onto CKM fire-rated T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.