

CAPCO

QS SPECIFICATIONS

EXPOSED TEE SUSPENDED CEILINGS

Thermoceil – 600 x 600 x 31mm Vinylclad Calcium Silicate Tiles with Thermal Insulation

Supply and install 600 x 600 x 31mm Thermoceil Ripple White vinylclad 6mm calcium silicate aluminium foil backed tiles with 25mm thick fire-retardant polystyrene adhered to back laid onto CKM T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

Thermoceil – 1200 x 600 x 31mm Vinylclad Calcium Silicate Tiles with Thermal Insulation

Supply and install 1200 x 600mm x 31mm Thermoceil Ripple White vinylclad 6mm calcium silicate aluminium foil backed tiles with 25mm thick fire-retardant polystyrene adhered to back laid onto CKM T38/24W pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.