

CAPCO

QS SPECIFICATIONS

EXPOSED TEE SUSPENDED CEILINGS

CAPCO Thermatex Star Mineral Fibre Acoustic Tiles – 600 x 600 x 15mm (White)

Supply and install CAPCO Thermatex Thermofon pre-painted white acoustic mineral fibre ceiling tiles 600 x 600 x 15mm with square edge laid onto Capco T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.

CAPCO Thermatex Star Mineral Fibre Acoustic Tiles – 1200 x 600 x 15mm (White)

Supply and install CAPCO Thermatex Thermofon pre-painted white acoustic mineral fibre ceiling tiles 1200 x 600 x 15mm with square edge laid onto Capco T38/24W 38 x 24mm pre-painted white exposed tee grid system. Main tees suspended by means of 19 x 0,5mm GMS strap hangers at 1,200m centres with 4,2 x 13mm wafer-tek screws to tees and 6 x 40mm express nails and M6 washers to slab. All in accordance with CAPCO and SABISA installation instructions.