

AMF TOPIQ® PRIME

AMF TOPIQ® Prime is a very light stone wool panel with a modern, smooth surface.

FEATURES

- Excellent sound absorption (0.95 αw)
- Excellent light reflectance (88%)
- ISO 5
- Ideal for offices, retail, classrooms, learning applications and underground garages

SPECIFICATIONS

Edge details	Board 
Thickness (mm)	15mm
Dimensions (mm)	600 x 600  1200 x 600 
System	Exposed Tee Ceiling Systems
Weight	2.4 kg / m²
Colour	White
Sound attenuation	EN ISO 10848-2 $D_{n,f,w}$ = 24 dB as per EN ISO 717-1 CAC = 24 dB as per ASTM E 413-10
Indoor air quality	A E1 IACG
Cleanability	

Sound absorption	EN ISO 354 α_w = 0.80 (H) as per EN ISO 11654 - Class B

Frequency f(Hz)	125	250	500	1000	2000	4000
α_p	0.50	0.85	0.95	0.90	1.00	1.00

NRC = 0.90 as per ASTM C 423

Sound reduction	EN ISO 10140-2 R_w = 13 dB as per EN ISO 717-1
Fire reaction	Euroclass A1 as per EN 13501-1 Class A as per ASTM E 84
Light reflectance	88%
Thermal conductivity	λ = 0.040 W/m K as per EN 12667
Humidity resistance	100% RH
Clean room	ISO 5 as per EN ISO 14644-1
Sustainability	28.4% www.blauer-engel.de/uz132

KZN:
2 Corobrik Place, Riverhorse Valley Business Estate, Durban.
Tel: 031 569 6090

BALLITO:
2 Apex Drive, North Point, R102, Shakas Head, Ballito.
Tel: 032 947 0422

GAUTENG:
21 Flower Close, Tunney, Germiston.
Tel: 011 822 8142

WESTERN CAPE:
Unit 6 Oude Molen Park
7 Oude Molen Road
Ndabeni, Cape Town
Tel: 021 002 7038

CAPCO
CEILING AND PARTITION COMPONENTS
www.capco.co.za